US009636811B2

(12) **United States Patent**
Segura

(10) **Patent No.: US 9,636,811 B2**
(45) **Date of Patent: May 2, 2017**

(54) **ACTUATION LOCKOUT FOR A FASTENER-DRIVING TOOL**

(71) Applicant: **Illinois Tool Works Inc.**, Glenview, IL (US)

(72) Inventor: **Ricardo Segura**, Lake in the Hills, IL (US)

(73) Assignee: **Illinois Tool Works Inc.**, Glenview, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 655 days.

(21) Appl. No.: **13/792,783**

(22) Filed: **Mar. 11, 2013**

(65) **Prior Publication Data**

US 2014/0252060 A1 Sep. 11, 2014

(51) **Int. Cl.**
B25C 1/00 (2006.01)

(52) **U.S. Cl.**
CPC ***B25C 1/008*** (2013.01)

(58) **Field of Classification Search**
CPC B25C 1/043; B25C 1/046
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,543,987 A * 12/1970 Obergfell B25C 1/003 227/136
3,638,532 A 2/1972 Novak
4,784,308 A * 11/1988 Novak B25C 1/003 227/120
5,167,359 A * 12/1992 Frommelt B25C 1/188 227/8
5,240,161 A * 8/1993 Kaneko B25C 1/003 227/109
5,626,274 A * 5/1997 Shkolnikov B25C 1/005 227/109
5,683,024 A 11/1997 Eminger et al.
5,829,661 A * 11/1998 Hirtl B25C 1/184 227/10
6,170,730 B1 * 1/2001 Lin B25C 1/003 227/119

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1 693 160 A1 8/2006
EP 1 862 262 B1 12/2009

Primary Examiner — Hemant M Desai
Assistant Examiner — Tanzim Imam
(74) *Attorney, Agent, or Firm* — Neal, Gerber & Eisenberg LLP

(57) **ABSTRACT**

A fastener-driving tool including a housing, a power source including a reciprocating driver blade, a tool nose configured for receiving the driver blade for driving fasteners fed into the nose and a magazine configured to house a collation including a plurality of the fasteners. A workpiece contact element is movably connected to the nose and moves between a rest position and an actuated position when the workpiece contact element is pressed against a workpiece, the workpiece contact element moves to the actuated position. A lockout mechanism is operatively associated with the workpiece contact element and the magazine, and is in contact with the collation in a first position when fasteners are in the magazine and moves to a second position when a last fastener in the collation has been driven by the driver blade to block the workpiece contact element and prevent further actuation of the tool.

17 Claims, 15 Drawing Sheets